

Model:
KBM3R

Traditional Reach-In's: Reach-In Solid Swing Door Refrigerator



KBM3R

- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
Heavy-duty pull handle
Each door with two spring hinges, this make the door self-closing with with enduring quality
- **R290 Refrigeration system** holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- **Electronic control system:**
Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath


Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
KBM3R	3	9	80-7/8 2054	32-1/4 818	82-1/2 2095	72 2040	3/4+	115/60/1	10.68	5-15P 

Plug type varies by country.



CONFORMS TO NSF/ANSI STD. 7

KINTERA EQUIPMENT, LLC

Add: PO BOX 1186, MANSFIELD MA 02048

Tel: 833-546-8372 Website: <https://kinteraequipment.com> E-mail: info@kinteraequipment.com

KBM3R Plan View

